



# **ROCX** *breakers*

- Micro, Mini, Midi and Heavy ranges
- Designed for extreme conditions
- High quality and proven durability
- Noise reduction technology
- Fully shock absorbed
- Energy recovery system

[www.rocxbreakers.com](http://www.rocxbreakers.com)



**ROCX**  
*group*



## Specifications

Description		450IP	950IP	1850IPS	2650IPS	4050IPS	4650IPS
Excavator Wight Range	Ton	2.5-4.5	5.5-9.0	11-18	16-26	28-40	32-46
Operating Weight	Lbs.	450	800	1850	3300	5800	6400
Operating Pressure	bar	90-120	120-150	150-170	160-180	160-180	160-180
	psi	1280-1707	1707-2134	2134-2418	2276-2560	2276-2560	2276-2560
Required Flow	l/min	25-50	50-90	80-110	100-150	180-240	200-260
	gal/min	6.5-13	13-24	21-29	27-40	48-63	51-69
Tool Diameter	mm	53	75	100	135	155	165
	inch	2.087	2.953	3.937	5.315	6.102	6.102
Impact Energy	Ft Lbs.	750	1250	2500	5000	8000	10000
Gas Pressure (Back Head)	bar	16	16	16	16	16	16
	psi	N/A	232	232	232	232	232

Disclaimer: Specifications and features are subject to change for improvent in quality without prior notice. E & OE.

**Ph. 877.617.7368**



**610 Salt Road, Webster NY 14580**  
**sales@rocxgroup.com www.rocxbreakers.com**